

# OPPOSITE 1

indoor lighting

Luminaire for recessed installation in ceilings or ceiling grids  
 BODY: painted aluminum sheet, white painted steel frame; a version for 625x625mm ceilings also possible  
 DIFFUSER: microprismatic, UGRPOWER  
 SUPPLY: remote electronic ballast  
 3xS TECHNOLOGY: save money, save energy, save time



## Concave microprismatic PMMA diffuser, DALI version, white, 81° light distribution, UGR <19

5946061	OPPOSITE 1 IN 597	LED 3000K	4200 lm	230V AC	48W	5.50
5946261	OPPOSITE 1 IN 622	LED 3000K	4200 lm	230V AC	48W	5.60
5947061	OPPOSITE 1 IN 597	LED 4000K	4200 lm	230V AC	48W	5.00
5947261	OPPOSITE 1 IN 622	LED 4000K	4200 lm	230V AC	48W	5.60

## Concave microprismatic PMMA diffuser, ON/OFF version, white, 81° light distribution, UGR <19

5946001	OPPOSITE 1 IN 597	LED 3000K	4200 lm	230V AC	48W	5.50
5946201	OPPOSITE 1 IN 622	LED 3000K	4200 lm	230V AC	48W	5.60
5947001	OPPOSITE 1 IN 597	LED 4000K	4200 lm	230V AC	48W	5.50
5947201	OPPOSITE 1 IN 622	LED 4000K	4200 lm	230V AC	48W	5.60

## Specular faceted reflector, ON/OFF version, white, IP20, 24° light distribution, frameless system

5866001	OPPOSITE 1 OUT 597	LED 3000K	4200 lm	230V AC	48W	5.00
5866201	OPPOSITE 1 OUT 622	LED 3000K	4200 lm	230V AC	48W	5.00

5867001	OPPOSITE 1 OUT 597	LED 4000K	4200 lm	230V AC	48W	5.00
5867201	OPPOSITE 1 OUT 622	LED 4000K	4200 lm	230V AC	48W	5.00

Specular faceted reflector, ON/OFF version, white, IP20, 38° light distribution, frameless system

5866061	OPPOSITE 1 OUT 597	LED 3000K	4200 lm	230V AC	48W	5.00
5866261	OPPOSITE 1 OUT 622	LED 3000K	4600 lm	230V AC	48W	5.00
5867061	OPPOSITE 1 OUT 597	LED 4000K	4200 lm	230V AC	48W	5.00
5867261	OPPOSITE 1 OUT 622	LED 4000K	4200 lm	230V AC	48W	5.00